UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/808,586	03/25/2004	Hiroyuki Arai	16359-005001 / 720/SM/toh	4600
26171 7590 05/24/2007 FISH & RICHARDSON P.C.		7	EXAMINER	
P.O. BOX 1022			CHOW, YUK	
MINNEAPOLI	S, MN 55440-1022		ART UNIT PAPER NUMBER	
			2609	
			MAIL DATE	DELIVERY MODE
		•	05/24/2007	PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

	Application No.	Applicant(s)			
	10/808,586	ARAI ET AL.			
Office Action Summary	Examiner	Art Unit			
	Yuk C. Chow	2609			
The MAILING DATE of this communication appears on the cover sheet with the correspondence address Period for Reply					
A SHORTENED STATUTORY PERIOD FOR REPLY WHICHEVER IS LONGER, FROM THE MAILING DA  - Extensions of time may be available under the provisions of 37 CFR 1.13 after SIX (6) MONTHS from the mailing date of this communication.  - If NO period for reply is specified above, the maximum statutory period w  - Failure to reply within the set or extended period for reply will, by statute, Any reply received by the Office later than three months after the mailing earned patent term adjustment. See 37 CFR 1.704(b).	ATE OF THIS COMMUNICATIO 36(a). In no event, however, may a reply be ti rill apply and will expire SIX (6) MONTHS from cause the application to become ABANDONI	N. mely filed n the mailing date of this communication. ED (35 U.S.C. § 133).			
Status		·			
Responsive to communication(s) filed on  2a) ☐ This action is <b>FINAL</b> . 2b) ☑ This  3) ☐ Since this application is in condition for allowar closed in accordance with the practice under E	action is non-final.  nce except for formal matters, pr				
Disposition of Claims					
4) ☐ Claim(s) 1-20 is/are pending in the application. 4a) Of the above claim(s) is/are withdray 5) ☐ Claim(s) is/are allowed. 6) ☐ Claim(s) 1-20 is/are rejected. 7) ☐ Claim(s) is/are objected to. 8) ☐ Claim(s) are subject to restriction and/or	vn from consideration.				
Application Papers		1 *			
9) ☐ The specification is objected to by the Examine 10) ☑ The drawing(s) filed on 25 March 2004 is/are: a Applicant may not request that any objection to the Replacement drawing sheet(s) including the correction 11) ☐ The oath or declaration is objected to by the Examine 10.	a) $\square$ accepted or b) $\square$ objected drawing(s) be held in abeyance. Setion is required if the drawing(s) is objective.	ee 37 CFR 1.85(a). Dijected to. See 37 CFR 1.121(d).			
Priority under 35 U.S.C. § 119					
<ul> <li>12) Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).</li> <li>a) All b) Some * c) None of:</li> <li>1. Certified copies of the priority documents have been received.</li> <li>2. Certified copies of the priority documents have been received in Application No.</li> <li>3. Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).</li> <li>* See the attached detailed Office action for a list of the certified copies not received.</li> </ul>					
Attachment(s)  1) Notice of References Cited (PTO-892)  2) Notice of Draftsperson's Patent Drawing Review (PTO-948)  3) Information Disclosure Statement(s) (PTO/SB/08)  Paper No(s)/Mail Date May. 18, 2006: Nov. 09, 2004.	4) Interview Summan Paper No(s)/Mail D 5) Notice of Informal 6) Other:	Date			

Art Unit: 2609

### **DETAILED ACTION**

# Drawings

1. Figures 12-14 should be designated by a legend such as --Prior Art--because only that which is old is illustrated. See MPEP § 608.02(g). Corrected drawings in compliance with 37 CFR 1.121(d) are required in reply to the Office action to avoid abandonment of the application. The replacement sheet(s) should be labeled "Replacement Sheet" in the page header (as per 37 CFR 1.84(c)) so as not to obstruct any portion of the drawing figures. If the changes are not accepted by the examiner, the applicant will be notified and informed of any required corrective action in the next Office action. The objection to the drawings will not be held in abeyance.

# Specification

The specification is objected to as failing to provide proper antecedent basis for the claimed subject matter. See 37 CFR 1.75(d)(1) and MPEP § 608.01(o). Correction of the following is required: claims 5-7 recites the limitation "data X" and "data Y". There is insufficient antecedent basis for this limitation in the claim.

### Claim Rejections - 35 USC § 112

- The following is a quotation of the second paragraph of 35 U.S.C. 112:
   The specification shall conclude with one or more claims particularly pointing out and distinctly claiming the subject matter which the applicant regards as his invention.
- 3. Claims 2, 4-7 are rejected under 35 U.S.C. 112, second paragraph, as being indefinite for failing to particularly point out and distinctly claim the subject matter which applicant regards as the invention.

Art Unit: 2609

In claims 2, 4-7, recites "TW", there isn't a clear definition for abbreviation "TW".

In claims 5-7, recites "data X" and "data Y" which are not clear, what are the composition of "data X" and "data Y"?

## Claim Rejections - 35 USC § 102

4. The following is a quotation of the appropriate paragraphs of 35
U.S.C. 102 that form the basis for the rejections under this section made in this
Office action:

A person shall be entitled to a patent unless -

- (b) the invention was patented or described in a printed publication in this or a foreign country or in public use or on sale in this country, more than one year prior to the date of application for patent in the United States.
- 5. Claims **1-15, 17-20** are rejected under 35 U.S.C. 102(b) as being anticipated by Hoekstra (US Patent 6,005,538).

As to claim 1, Hoekstra discloses a driving circuit (Fig. 3) for a vacuum fluorescent display having a filament (Fig. 3(26)), a grid electrode Fig. 3(24)) and a segment electrode (Fig. 3(20a-g)), the driving circuit comprising: a filament driving unit (Fig. 3(50)) for driving the filament; a grid driving unit (Fig. 3(46)) for pulse-driving the grid electrode; a segment driving unit (Fig. 3(42)) for pulse-driving the segment electrode; and a controlling unit (Fig. 5(92)) for validating or invalidating the output of the filament driving unit at a proper timing (Fig. 8).

As to claim 2, Hoekstra discloses a driving circuit for a vacuum fluorescent display according to claim 1, wherein in case of invalidating the output (Fig. 5 (60)) of the filament driving unit, the controlling unit invalidates (Col. 6 line 29, microcomputer **removes** the drive from transistor (Fig. 5(Q1)) which causes Q1

Art Unit: 2609

to open) the output of the filament driving unit for a time period TW (Fig. 8(A)) when a voltage is reached at which the grid electrode and the segment electrode are driven by the grid driving unit and the segment driving unit, respectively, and when the time period TW to reach the voltage is shorter than a predetermined time period (Col. 6 lines 19-59).

As to claim 3, Hoekstra discloses a driving circuit for a vacuum fluorescent display according to claim 2, wherein the controlling unit outputs (Fig. 5(44,48)) a pulse driving signal for pulse-driving the filament (Col. 5 line 62-Col. 6 line18).

As to claim **4**, Hoekstra discloses a driving circuit for a vacuum fluorescent display according to claim 2, wherein during the time period TW (Fig. 8(A)) shorter than the predetermined time period, the controlling unit fixes (Col. 6 line 36, ...*causing* the filament to *ride* at...) the output of the filament driving unit at a predetermined level (Fig. 5(-V<sub>kk</sub>), also see Col. 6 lines 31-34).

As to claim **5**, Hoekstra discloses a driving circuit for a vacuum fluorescent display according to claim 2, wherein the driving circuit for a vacuum fluorescent display enables the output of the filament driving unit to be set invalid when it is at some logic value (Fig 5(48)), the driving circuit receiving from exterior data X (Fig. 5(60)) that enables the output of the filament driving unit to be set valid when it is at another logic value (OFF), and wherein the controlling unit (Fig. 5(92)): sets the output of the filament driving unit invalid for the time period TW (Fig. 8(A)) that is shorter than the predetermined time period when the data X (Fig 5(48)) received from the exterior is at the some logic value (on); and sets the

output of the filament driving unit valid when the data X received from the exterior is at the other logic value (Col. 5 line 61-Col. 6 line 18).

As to claim **6**, Hoekstra discloses a driving circuit for a vacuum fluorescent display according to claim 5, wherein the driving circuit for a vacuum fluorescent display receives from an exterior data Y (Fig. 5(98)) correlated with the duty ratio of the output of the grid driving unit or the output of the segment driving unit, and wherein the time period TW is a time period of the pulse width based on the duty ratio corresponding to the received data Y (Col. 6 lines 19-59).

As to claim 7, Hoekstra discloses a driving circuit for a vacuum fluorescent display according to claim 2, wherein the driving circuit for a vacuum fluorescent display receives from exterior data Y (Fig. 5(98)) correlated with the duty ratio of the output of the grid driving unit or the output of the segment driving unit, and wherein the controlling unit (Fig. 5(92)) invalidates the output of the filament driving unit for the time period TW when the time period TW based on the duty ratio corresponding to the received data Y is equal to or shorter than a predetermined time period (Col. 6 lines 19-59).

As to claim **8**, Hoekstra discloses a driving circuit for a vacuum fluorescent display according to claim 2, wherein the driving circuit for a vacuum fluorescent display is a semiconductor integrated circuit (Fig. 5(92)), the driving circuit enabling a switching element (Fig. 5(Q1)) that generates a voltage (Fig. 8(5V)) for pulse-driving the filament to be connected to exterior based on the output (Fig. 5(44) of the filament driving unit (Col. 5 line 61-Col. 6 line 18).

Art Unit: 2609

As to claim **9**, Hoekstra discloses a driving circuit for a vacuum fluorescent display according to claim 2, comprising a switching element (Fig. 5(Q1)) that generates a voltage (Col. 6 line 6-14) for pulse-driving (Col. 6 line 20) the filament based on the output of the filament driving unit (Col. 5 line 61-Col. 6 line 18).

As to claim **10**, Hoekstra discloses a driving circuit for a vacuum fluorescent display according to claim 9, wherein the driving circuit for a vacuum fluorescent display is a semiconductor integrated circuit (Fig. 5(92), the driving circuit enabling the switching element (Fig. 5(Q1)) to be connected (Fig. 5(C2, R32)) to exterior.

As to claim 11, Hoekstra discloses a driving circuit for a vacuum fluorescent display according to claim 9, wherein the driving circuit for a vacuum fluorescent display is a semiconductor integrated circuit integrated (Fig. 7(90) with the switching elements (Col. 7 lines 46-59).

As to claim **12**, Hoekstra discloses a driving circuit for a vacuum fluorescent display according to claim 1, wherein when validating the output (Fig. 3(60)) of the filament driving unit (Fig. 3(50)), the controlling unit enables a pulse width and/or a pulse cycle of a pulse (Col. 6 line 20) driving signal for pulsedriving the filament to be set based on data (Fig. 5(44) received from exterior.

As to claim 13, Hoekstra discloses a driving circuit for a vacuum fluorescent display according to claim 12, wherein the data received from exterior includes pulse width data (Fig. 8(A)) for setting the pulse width of the pulse driving signal, and wherein the controlling unit generates the pulse (Col. 6 line

Art Unit: 2609

20) driving signal having a pulse width corresponding to the received pulse width data (Col. 6 lines 19-59).

As to claim **14**, Hoekstra discloses a driving circuit for a vacuum fluorescent display according to claim 12, wherein the data received from exterior includes pulse cycle data (Fig. 8) for setting the pulse cycle of the pulse driving signal, and wherein the controlling unit generates the pulse driving signal having a pulse cycle corresponding to the received pulse cycle data (Col. 4 lines 13-51).

As to claim 15, Hoekstra discloses a driving circuit for a vacuum fluorescent display according to claim 12, wherein the data (Fig. 5(44) received from exterior includes pulse width data (Fig. 8) for setting the pulse width (Fig. 8(A)) of the pulse driving signal and pulse cycle data (Fig. 5(60)) for setting the pulse cycle of the pulse driving signal, and wherein the controlling unit sets the pulse width and/or the pulse cycle of the pulse driving signal by putting the pulse driving signal at one level (Col. 6 line 27, duty cycle does not exceed 50%...) for a time period of the pulse width corresponding to the received pulse width data, and by putting the pulse driving signal at another level (Col. 6 line 48, between 50-80%) for a time period other than the pulse width among the pulse cycles corresponding to the received pulse cycle data (Col. 6 lines 19-59).

As to claim 17, Hoekstra discloses a driving circuit for a vacuum fluorescent display according to claim 12, wherein the driving circuit for a vacuum fluorescent display is a semiconductor integrated circuit (Fig. 5(92), the driving unit enabling the switching element (Fig. 5(Q1)) that generates a voltage (Fig.

Art Unit: 2609

8(5V)) for pulse-driving the filament based on the pulse driving signal (Fig. 5(R32,C2)) to be connected to the exterior (Fig. 5(92)).

As to claim **18**, Hoekstra discloses a driving circuit for a vacuum fluorescent display according to claim 12, wherein the driving circuit for a vacuum fluorescent display comprises a switching element (Fig. 5(Q1)) that generates a voltage (Fig. 8(5V)) for pulse-driving the filament based on the pulse driving signal (Fig. 5(R32,C2)).

Regarding claims **19,20**, limitations within these claims are identical to claims **10, 11** respectively. Therefore, same rejections apply to these claims.

# Claim Rejections - 35 USC § 103

- 6. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:
  - (a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.
- 7. Claim **16** is rejected under 35 U.S.C. 103(a) as being unpatentable over Hoekstra (US Patent 6,005,538) in view of Harris (US Patent 4,968,917).

As to claim **16**, Hoekstra discloses a driving circuit for a vacuum fluorescent display according to claim 15 above.

However, Hoekstra does not teach a first comparing unit for comparing the pulse width data with a count value based on a reference clock signal; a second comparing unit for comparing the pulse cycle data with a count value based on a reference clock signal; a counting unit for generating the count

Art Unit: 2609

value by dividing as predetermined the reference clock signal as well as resetting the count value when the result of the comparison at the first comparing unit or the second comparing unit shows coincidence; and a **controlling unit** for putting the pulse driving signal at one level when the result of the comparison at the first comparing unit shows coincidence, and for putting the pulse driving signal at the other level when the result of the comparison at the second comparing unit shows coincidence.

Harris discloses a dimmer controller for VFD wherein utilizes a dual comparator (Fig. 1(35)), a controlling unit (Fig. 1(40)) which also function as a count unit (Col. 4 lines 19-42).

It would have been obvious to one of ordinary skill in the art at the time the invention was made to utilize dual comparator circuit of Harris into vacuum fluorescent display driver of Hoekstra, because it would improve the usability of control circuit and offer finer adjustment to the brightness level as suggested by Harris (Col. 1 line 64- Col. 2 line 61).

#### Conclusion

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Yuk C. Chow whose telephone number is 571 270-1544. The examiner can normally be reached on 8-6 M-TH E.T..

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Amare Mengistu can be reached on 571 270-1550. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Art Unit: 2609

Page 10

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

yc

AMARE MENGISTU
SUPERVISORY PATENT EXAMINER